

NEW TO THE **STREAMLINE**[®] RANGE

STREAMFLO[™]

The new name for reliable, on-demand, positive displacement diaphragm pumps with pressure switch protection

Pump features

- Self-priming
- Corrosion resistant built-in check valve
- Silent running and smooth operation
- Can run dry for short periods of time without damage



SF.DP22-012-100-238 Specification

- Pressure switch setting - 100psi (6.9bar)
- Open flow - 4.5lpm (1.2 gpm)
- Max temp - 70°C
- Inlet/Outlet - 3/8" NPT female ports
- Power requirement - 12v DC



SF.DP34-016-100 Specification

- Pressure switch setting - 100psi (6.9bar)
- Open flow - 6.0lpm (1.6gpm)
- Max temp - 70°C
- Inlet/Outlet - 1/2" NPT male ports
- Power requirement - 12v DC

DO NOT USE TO PUMP FLAMMABLE LIQUIDS

PART NO.	DESCRIPTION
SF.DP22-012-100-238	StreamFlo [™] Pump 12v 100psi 4.5lpm 3/8F threaded ports
SF.DP34-016-100	StreamFlo [™] Pump 12v 100psi 6.0lpm 1/2 inch male ports

PUREGLAZE CLEANING SYSTEMS CC.

335 Ontdekkers Road
Florida Park, Roodepoort, 1709
Tel +27 (011) 768 1100
Email sales@pureglaze.co.za
Web www.pureglaze.co.za

STREAMLINE[®]

Specialist Cleaning Solutions